

Removal of Iron(II) Using Ni/Al Layered Double Hydroxide Intercalated with Keggin Ion

Title	Removal of Iron(II) Using Ni/Al Layered Double Hydroxide Intercalated with Keggin Ion
Author Order	5 of 6
Accreditation	1
Abstract	Layered double hydroxide (LDH) Ni/Al-NO ₃ was synthesized using a coprecipitation method under base condition following with intercalation using Keggin ion [a-SiW ₁₂ O ₄₀] ⁴⁻ to form Ni/Al-[a-SiW ₁₂ O ₄₀] LDH. The LDHs were characterized using XRD, FTIR, BET, and pH _{pzc} analyses. Furthermore, LDHs were applied as adsorbent of iron(II) from aqueous solution. The adsorption process was studied through the effect of adsorption time, the concentration of iron(II), and temperature adsorption. The results show the interlayer distance of LDHs was increased from 7.408 Å to 10.533 Å after intercalation process. The adsorption of iron(II) on LDHs showed that adsorption of iron(II) on both LDHs follows pseudo first-order kinetic model with R ² value is close to one. The adsorption process was spontaneous, with adsorption capacity up to 36.496 mg g ⁻¹ .
Publisher Name	Universitas Jenderal Soedirman
Publish Date	2020-11-27
Publish Year	2020
Doi	DOI: 10.20884/1.jm.2020.15.3.600
Citation	
Source	Molekul
Source Issue	Vol 15, No 3 (2020)
Source Page	149-157
Url	https://ojs.jmolekul.com/ojs/index.php/jm/article/view/600/343
Author	ROY ANDREAS, S.Si, M.Si, Ph.D